

Pulse All-In-One

An affordable and reliable All In One







Specifications

- Intel Atom 1.6 Ghz CPU
- Up to 2 Gig Ram
- 15" LCD with Resistive Touch Screen
- Fanless Ideal for Harsh Environments

Optional Peripherals

- Integrated MSR
- Integrated 2 x 20 Customer Display
- Integrated Rear 8 or 12" LCD

Designed to Provide High Value with Outstanding Reliability

The Pulse All-In-One system is designed to offer flexibility and reliability at an affordable price. The Pulse supports Intel Atom 1.6 CPU. The Pulse AIO boasts a quick detachable base and easy overall service features. A 15" LCD with Resistive Touch Screen and up to 2 GB of RAM, this fanless system is ideal for harsh environments. The Pulse All-In-One offers a variety of add-on options including, integrated MSR, a 2 x 20 customer display and an integrated rear 8" or 12" LCD.







Processing

- CPU Intel Atom N270 processor 1.6GHz L2 512K FSB 533MHz
- Chipset Intel 945GSE Express + ICH7M
- System Memory 1 x DDR2 DIMM up to 2GB
- Graphic Memory Intel GMA 950 share system memory up to 224MB
- BIOS AWARD PnP

LCD Panel

- LCD Size 15"
- Brightness (cd/m2)- 250 nits
- Maximum Resolution 1024 x 768
- Touch Screen Type Resistive
- Tilt Angle (degree) 0° ~ 85°

Storage

• HDD - one 2.5 SATA HDD, SSD or Compact Flash

Power

- Power Supply 65W 19V power adapter
- EMC & Safety FCC / CE Class A, LVD
- Operating Temperature 5°C ~ 35°C (41°F ~ 95°F)

Expansion

• Mini-PCle Slot - 1

I/O Ports

- USB 4 (USB 2.0)
- Serial 4 x RJ45 with 2 DB9 Adapters (Com 3 & 4 Powered with 5V/12V, selectable by jumper)
- Gigabit LAN (10/100/1000) 1
- Cash Drawer Port 1 RJ11 (12v / 24v)
- DC Jack = 1
- Power Button 1
- PS2 1 (optional)
- Audio Out (optional)

Optional Peripherals

- MSR (PS2)
- MSR/URU Biometric Reader
- Rear LCD 8.4" or 12.1"
- Customer Display 2 x 20 VFD Display
- Speakers 2 x 2W
- Wireless LAN 802.11 a/b/g/n







